

AQUA 20



GENERAL INDUSTRY

Water/Discharge applications



APPLICATIONS

Heavy duty water delivery hose, for irrigation, industrial or waste water.


TECHNICAL DESCRIPTION

Inner tube	SBR, black, smooth.
Reinforcement	synthetic textile
Cover	SBR, black, fabric impression.
Temperature range	-30°C => +80°C



TRELLEBORG

AQUA 20





GENERAL INDUSTRY

AQUA 20



ID (MM)	OD (MM)	WORKING PRESSURE (BAR)	BURSTING PRESSURE (BAR)	WEIGHT (KG/M)	LENGTH (M)	ARTICLE NUMBER
25.0	35.0	20	60	0.71	40	5503689
32.0	42.0	20	60	0.95	40	5503690
38.0	48.0	20	60	1.08	40	5503691
51.0	61.0	20	60	1.22	40	5503692
63.0	74.0	20	60	1.71	40	5503693
76.0	87.0	20	60	1.90	20	59007840
76.0	87.0	20	60	1.90	40	5503694
80.0	91.0	20	60	2.09	20	59007841
80.0	91.0	20	60	2.09	40	5503721
90.0	101.0	20	60	2.39	20	59007842
90.0	101.0	20	60	2.39	40	5503722
102.0	114.0	20	60	2.80	20	59007843
102.0	114.0	20	60	2.80	40	5503686
152.0	168.0	18	54	9.13	20	59007845
152.0	168.0	18	54	9.13	40	5503687
203.0	223.0	18.0	54.0	14.70	20	59007846

Tolerance on length: $\pm 1\%$ (ISO 1307 Standard).

